CS 150 (Closed-book) Midterm Test I

Oct. 28, Wed., 7:10-7:50pm, 2026

Total: 40 points

Name:

UCR Net ID:

QUESTION 1. [10 pts] Design a DFA to accept the following language:

$$L = \{x \mid x \in \{0,1\}^*, \text{ the number of } 0'\text{s in } x \text{ is divisible by 2 and the number of } 1'\text{s in } x \text{ is divisible by 4}\}$$

Answer:

	0	1
$* \rightarrow q_{0,0}$	$q_{1,0}$	$q_{0,1}$
$q_{0,1}$	$q_{1,1}$	$q_{0,2}$
$q_{1,0}$	$q_{0,0}$	$q_{1,1}$
$q_{1,1}$	$q_{0,1}$	$q_{1,2}$
$q_{0,2}$	$q_{1,2}$	$q_{0,3}$
$q_{1,2}$	$q_{0,2}$	$q_{1,3}$
$q_{0,3}$	$q_{1,3}$	$q_{0,0}$
$q_{1,3}$	$q_{0,3}$	$q_{1,0}$

Give partial credits for DFAs that handles the number of 0's or the number of 1's correctly.

QUESTION 2. [10 pts] Design an ϵ-NFA to accept the following language:

$$L = \{x \mid x \in \{0,1\}^*,\ x \ \text{ begins or ends with } 100\}$$

Answer:

	ϵ	0	1
$\rightarrow q_0$	$\{q_1, q_2\}$	$\emptyset$	$\emptyset$
q_1	$\emptyset$	$\emptyset$	$\{q_3\}$
q_3	$\emptyset$	$\{q_5\}$	$\emptyset$
q_5	$\emptyset$	$\{q_7\}$	$\emptyset$
$^*q_7$	$\emptyset$	$\{q_7\}$	$\{q_7\}$
q_2	$\emptyset$	$\{q_2\}$	$\{q_2, q_4\}$
q_4	$\emptyset$	$\{q_6\}$	$\emptyset$
q_6	$\emptyset$	$\{q_8\}$	$\emptyset$
$^*q_8$	$\emptyset$	$\emptyset$	$\emptyset$

Note that the answer is not unique, and it is also possible to design an NFA for the language without using ϵ-transitions or even a DFA.

QUESTION 3. [10 pts] Convert the following NFA to a DFA:

	0	1
$\rightarrow q_0$	$\{q_1\}$	$\{q_0, q_1\}$
q_1	$\{q_1, q_2\}$	$\{q_2\}$
$^*q_2$	$\{q_1\}$	$\emptyset$

Answer:

	0	1
$\rightarrow \{q_0\}$	$\{q_1\}$	$\{q_0, q_1\}$
$\{q_1\}$	$\{q_1, q_2\}$	$\{q_2\}$
$^*\{q_2\}$	$\{q_1\}$	$\emptyset$
$\{q_0, q_1\}$	$\{q_1, q_2\}$	$\{q_0, q_1, q_2\}$
$^*\{q_1, q_2\}$	$\{q_1, q_2\}$	$\{q_2\}$
$^*\{q_0, q_1, q_2\}$	$\{q_1, q_2\}$	$\{q_0, q_1, q_2\}$
$\emptyset$	$\emptyset$	$\emptyset$

It's okay to includue inaccessible states (*i.e.*, $\{q_0, q_2\}$). Give partial credits for correct steps.

QUESTION 4. [10 pts] Give a regular expression for the following language:

$$L = \{x \mid x \in \{0,1\}^*,\ x \text{ has at most three } 0'\text{s between consecutive } 1'\text{s}\}$$

For example, the language constains strings $00, 010000, 001000100101110000$, but not strings like 0100001 or 100101100000111.

Answer:

$$0^* + 0^*1((\epsilon + 0 + 00 + 000)1)^*0^*$$

The regex is not unique. Give partial credits for regex's containing some correct components.